



January 1997

V/UHF Miniceptor Receivers WJ-860X & WJ-860XA

3-GHz Frequency Extender Option 860X/3GFE & 860XA/3GFE

Specifications

Preselection	9 sub-octave filters (512 MHz to 3 GHz)
Noise Figure	15 dB, max (512 MHz to 3 GHz)
Intermodulation*	2nd Order +35 dBm (512 MHz to 3 GHz) 3rd Order 0 dBm (512 MHz to 3 GHz)
Image Rejection	80 dB, min 90 dB, typical*
IF Rejection	75 dB, min*
Phase Noise	-88 dBc/Hz (512 to 1410 MHz) -85 dBc/Hz (1410 to 3000 MHz)*
Tuning Time	5 mSec when tuning from non-FE to FE frequency 1 mSec typical tuning within the 512-MHz to 3-GHz range
Power Consumption	5 W*
Weights & Dimension	*

*Same as 2-GHz extender

Note: All performance specifications apply to the 3-GHz frequency extender when operating with the Miniceptor receiver.

WATKINS-JOHNSON COMPANY
700 Quince Orchard Road, Gaithersburg, Maryland 20878-1794
Phone: (800) WJHELPS or +(301) 948-7550
FAX: +(301) 921-9479 Email: wj.helps@wj.com Website: www.wj.com

All International sales of WJ equipment are subject to USA export license approval.
This material provides up-to-date general information on product performance and use. It is not contractual in nature, nor does it provide warranty of any kind.